



## 6 MP Outdoor 36X Speed PTZ Camera with 3 KM Laser Illumination .

SensorTec 6 MP PTZ ensures a high resolution and a 25 FPS speed. Camera provides effective manual target tracking thanks to its fast positioning and high accuracy within a 360° horizontal and 100° vertical range. Its image sensor delivers wide dynamic range images. The picture quality and the 36x optical zoom of the camera makes it possible to provide close-ups of the areas of interest and target objects. As the PTZ has a unique integrated IR Laser illuminator with an automatic cooperating focus system, it is able to provide quality images of monitored targets even in low lighting conditions. Specially developed PTZ control functions in SensorTec Control Center, such as mouse controlled joystick emulation, the PointIT control function or PTZ position bookmarks make monitoring convenient and easy.

### KEY FEATURES

- 6 MP resolution
- 1" size sensor
- Wide Dynamic range
- 3 KM Laser illumination
- images 36x optical zoom
- IR Laser illumination with automatic cooperating focus system
- 3D Privacy mask
- Multi-zone video motion detection analytics
- IP66 rated outdoor enclosure
- Fast and accurate positioning
- Specially developed control functions in SensorTec Control Center
- JPEG2000 wavelet-based, visually lossless compression
- Integrated cleaning system (Wiper + Washer)  
Water tank is a separate unit

### RESOLUTION SPECIFICATION

Human Identification Distance	600 ppm	146 m
Human recognition Distance	250 ppm	350 m
Human detection Distance	25 ppm	3500 m

### SPECIALLY DEVELOPED FUNCTIONS IN SENSORTEC CONTROL CENTER

- Precise positioning with simple mouse click
- PTZ history
- PTZ zoom control by area selection
- Joystick emulation control with mouse
- PTZ positioning on map
- GPS based positioning
- Interactive PTZ control on the panoramic image
- PTZ Position bookmarks
- Automatic PTZ tour with predefined parameters
- Zone violation detection and immediate alarm (in cooperation with a VCA NVR)
- Abandoned object detection and immediate alarm (in cooperation with a VCA NVR)
- Detecting suspicious behaviors and immediate alarm (in cooperation with a VCA NVR)
- Individually compressed frames
- Special picture enhancement algorithm for foggy, rainy weather conditions

### TECHNICAL SPECIFICATION

<b>Part number</b>	ST-6PTZ3KL
<b>Imaging</b>	
<b>Description</b>	SensorTec 6MP IP PTZ DN camera
<b>Day and Night</b>	ICR function for Day/Night switching, automatically removable infrared-cut filter
<b>Sensor</b>	CMOS Sony 1"
<b>WDR</b>	103 dB
<b>Scanning system</b>	Progressive, no interlaced scanning
<b>Video compression</b>	JPEG2000
<b>Image size</b>	3072 x 2048
<b>Frame rate</b>	Up to 25 FPS @ 6MP; all resolution
<b>Image settings</b>	Color, Brightness, White balance, Compression ratio, FPS, Exposure control, Real-time image enhancement, Text overlay
<b>Illuminations</b>	
<b>Minimum illumination</b>	Color: 0.75 lux (50 IRE AGC-OFF 1/10s 80%) 0.02 lux (50 IRE AGC-ON 1/2s 80%) B/W: 0.01 lux (50 IRE AGC-OFF 1/10s 80%) 0.001 lux 50IRE AGC-ON 1/2s 80%)
<b>IR Laser Illumination</b>	Varifocal IR Laser illuminator, 808 nm, 500W pulsed
<b>IR Laser illumination Range</b>	3000 Meter
<b>LENS</b>	
<b>Lens</b>	f = 6 mm - 210 mm; F = 1.5 - 4.3; Auto-focus, Auto-Iris
<b>Zoom</b>	36x Optical Zoom, 10x Digital zoom
<b>Angle of View</b>	Horizontal: 63.17° - 2.01° Vertical: 44.57° - 1.34°

<b>Pan Tilt</b>	
Horizontal range	0-360°
Vertical range	0-100°
Preset speed	400°/sec
Preset accuracy	± 0.10°
Preset positions	100, selectable default preset
Guard tour	Unlimited, Schedule based
Privacy mask	3D Privacy mask
<b>Event Trigger</b>	
Analytics	Video motion detection, multi-zone
Event triggers	Live stream access, Archive stream accessed, Video motion detection, Network, Camera Settings, Temperature, Input trigger, Preset reached
<b>Audio</b>	
Sound	Built-in microphone, 1 ch external 24 kHz/16bit, sound in/output
Inputs/Outputs	4 programmable IO connections NO, NC / OC 0.5A/30V
<b>Network and Storage</b>	
Ethernet connection	1000 Mbit; RJ45
Network	TCP/IP
Network security	1500 bit public-key RSA; User authentication
Storage support	SensorTec Network Video Recorder
Approvals	EN 55022:2010/AC:2011, EN 61000-3-2:2014, EN 61000-3-3:2013,
	EN 50130-4:2011/A1:2015, EN 55013:2013, EN 55024:2010,
	IEC/EN 60529 IP66

#### MECHANICAL SPECIFICATION

Material	Full metal casing Aluminum alloy, glass windows
Dimensions (W x D x H)	205 × 312 × 386 mm (with mounting bracket)
Package dimensions (W x D x H)	290 × 300 × 410 mm
Master carton dimensions (W x D x H)	630 × 630 × 450 mm
Pieces / Master carton	4 pcs

### APPLICATION AREAS

SensorTec 6 MP PTZ camera makes it possible to effectively monitor medium or large-scale areas both indoors and outdoors. The camera delivers a resolution that is high enough for face recognition even at hundreds of meters distance therefore it is the ideal component of surveillance solutions. SensorTec PTZ camera can be effectively used together with SensorTec Panorama camera as it can be controlled on the panoramic images by selecting an area of interest. As it is possible to monitor streets, parks or large scale urban areas easily with these cameras, they are the essential parts of SensorTec city, safe and smart city, airport, border control and critical infrastructure surveillance solutions.

- **Safe and Smart City**
- **City Video Surveillance**
- **Airport Video Monitoring**
- **Border Surveillance**
- **Critical Infrastructure Video**